

NPAD-OB SERIES

PANEL DIFFUSERS — WITH REMOVABLE CORE



NPAD 1—OB—One way

NPAD 2—OB—Two way

NPAD 2C—OB—Two way corner throw

NPAD 3—OB—Three way

NPAD 4—OB—Four way

OPTIONAL: Available without opposed blade damper as model NPAD.

DESIGN: The NPAD-OB Series consists of a flush frame pattern diffuser mounted in a panel sized to match standard T-bar ceilings. The integral unit is, in turn, designed for lay-in type, grid ceilings, resulting in an extremely attractive, uncluttered ceiling. The core is removable. Opposed blade dampers allow precise volume adjustment.

FEATURES: Diffuser neck sized to fit within NOMINAL DUCT sizes. Easily removable SNAP-IN CENTER CORE cuts installation time. CORNER KEY construction prevents open mitres and provides increased rigidity. Entire unit assembly by mechanical means—no spotwelds to break. Panel sized to fit within nominal dimensions—no ceiling grid alterations. Opposed blade dampers controlled by lever accessible from face of installed unit. **UNIQUE CIRCULAR AIR PATTERNS.**

CONSTRUCTION: Diffuser constructed of Aluminum extrusion throughout, except: (NOTE A) center cone, in square configurations only, is stamped aluminum alloy 1100. In rectangular configurations, the center cone is extruded aluminum. Neck sizes in 3" increments. Painted white is standard. Panel constructed of heavy duty galvanized steel.

APPLICATION: Designed specifically for lay-in type grid ceiling systems, where esthetics demand smooth, uncluttered appearance in addition to precise volume control.

