

PERF SERIES
PERFORATED DIFFUSERS
SURFACE MOUNT



AVAILABLE
PERF-R Series
 Perforated return
 surface mount

PERF-1 – One way
PERF-1-OB – (w/damper)

PERF-2C – Two way (corner)
PERF-2 COB – (w/damper)

PERF-4 – Four way
PERF-4OB – (w/damper)

PERF-2 – Two way
PERF-2-OB – (w/damper)

PERF-3 – Three way
PERF-3 OB – (w/damper)

DESIGN: The PERF Series are perforated face supply diffusers designed for ceiling application. A high degree of air pattern direction is obtained by use of individually adjustable blades mounted behind the perforated face plate.

FEATURES: Highly attractive appearance blends with any ceiling decor.
PERFORATED PLATE evenly diffuses air, eliminating drafts.
CONCEALED SUPPLY BLADES impart adequate direction to leaving air.
CONCEALED HINGE and tension spring assembly allow easy disassembly of face plate for cleaning.
 Unique **CORNER KEY** construction ensures tightly closed corners and extreme durability.
 Mechanical assembly used throughout—no spot welds to break.
 Model OB dampers available factory installed (optional).
 Matching return, Model PERF-R available.

CONSTRUCTION: Diffuser constructed of aluminum extrusions, perforated panel of steel.
 Frame thickness .050"
 Furnished in off-white enamel.

APPLICATION: For ceiling application, the PERF series is unmatched for a smooth, uncluttered appearance. The design, with the many available configurations, allows on-the-job adjustment of discharge patterns to suit virtually any requirement.

